

dBi HART INTELLIGENT TRANSDUCERS

Technical Specifications:

The Pulsar dBi HART Transducer Series is a range of self-contained, intelligent, non-contacting ultrasonic level measurement transducers which make use of HART communication protocols to make plant integration simple.



PHYSICAL: TRANSDUCER SPECIFIC:

	dBi3	dBi6	dBi10	dBi15
Sensor Body Dimensions:	77 mm D x 134 mm H (3 in x 5.3 in)	86 mm D x 121 mm H (3.4 in x 4.8 in)	86 mm D x 121 mm H (3.4 in x 4.8 in)	86 mm D x 121 mm H (3.4 in x 4.8 in)
Weight:	1 kg (2.2 lb)	1.2 kg (2.7 lb)	1.3 kg (2.9 lb)	1.4 kg (3.1 lb)
Measurement Range:	125 mm to 3 m (4.9 in to 9.8 ft)	300 mm to 6 m (11.8 in to 19.7 ft)	300 mm to 10.1 m (11.8 in to 32.8 ft)	500 mm to 15 m (19.7 in to 49.2 ft)
Frequency:	125kHz	75kHz	50kHz	41kHz
Beam Angle:	< 10°	< 10°	< 10°	< 8°
Accuracy	2 mm (0.08 in)	4 mm (0.2 in)	3 mm (0.1 in) up to 6 m (19.7 ft) range 6 mm (0.2 in) over 6 m (19.7 ft) range	5 mm (0.2 in) up to 10 m (32.8 ft) 10 mm (0.4 in) over 10 m (32.8 ft) range
Resolution:	1 mm (0.04 in)	2 mm (0.08 in)	3 mm (0.1 in)	5 mm (0.2 in)

PHYSICAL: ALL TRANSDUCERS

Sensor Body Material:	Valox 357 PBT
Cable Lengths:	Standard: 5 m, 10 m, 20 m, or 30 m (16.4 ft, 32.8 ft, 65.6 ft, or 98.4 ft) Optional up to 150 m (492.1 ft) maximum (increments of 10 m (32.8 ft) only)
Mounting Connection:	1" BSP or 1" NPT

ENVIRONMENTAL

Enclosure Protection:	IP68 / NEMA 6P
Max. And Min. Temperature (Electronics):	-40 °C to +80 °C (-40 °F to +176 °F), options for front thread and flange mounting

PERFORMANCE

Input voltage range:	10-28 V DC
Output:	4-20mA output, resolution 1µa
Current Consumption:	3.8-22mA
Boot Time:	From power-up to stable reading: Cold boot = 8 seconds, Warm boot (within 12 hours from last start-up) = 4 seconds
Communications Protocol:	HART 7


APPROVALS

CE Approval: Listed in the Certificate of Conformity within the manual


ATEX Approval: Standard: Zones 1 & 2 to Ex II 2 G Ex mb IIC T4 Gb, Ex II 2 D Ex mb IIIC T130 °C Db, Tamb= -40 °C to +80 °C
Optional: Zone 0 to Ex II 1 G Ex ia IIC T4 Ga, Ex II 1 D Ex ia IIIC T130 °C Da, Tamb= -40 °C to +80 °C

TRANSDUCER OPTIONS


	dBi3	dBi6	dBi10	dBi15
PVDF:		✓	✓	
Front Threaded / PVDF:	✓	✓	✓	
Submergence Shield:	✓	✓	✓	✓
Flanged DIN / ANSI:		✓	✓	✓
Foam Face:			✓	✓
Sanitary Flange	✓	✓	✓	
Intrinsically Safe of All the Above:	✓	✓	✓	✓



dBi3 & dBi6 Front Thread




dBi3 Rear Thread



dBi10 Front Thread



dBi6 & dBi10 Rear Thread



dBi15 Rear Thread

Delivering the Measure of Possibility

Pulsar Measurement offers worldwide professional support for all of our products, and our network of global partners all offer full support and training. Our facilities in Malvern, UK and Largo, USA are home to technical support teams who are always available to answer your call or attend your site when required. Our global presence, with direct offices in the UK, USA, Canada, and Malaysia, allows us to create close relationships with our customers and provide service, support, training, and information throughout the lifetime of your product.

For more information, please visit our website:

www.pulsarmeasurement.com



INFO@PULSARMEASUREMENT.COM

Pulsar Measurement is a trading name of Pulsar Process Measurement Ltd.

*Copyright © 2021 Pulsar Measurement
Registered Address: 1 Chamberlain Square CS, Birmingham B3 3AX
Registered No.: 3345604 England & Wales*

United States
+1 888-473-9546

Asia
+60 102 591 332

Canada
+1 855-300-9151

Oceania
+61 428 692 274

United Kingdom
+44 (0) 1684 891371

pulsarmeasurement.com